



3PC Full Port Ball Valve Screwed-ends, PN63, PSI1000

- The head conform with EN 10226-1, ISO 7-1
- Blow-out proof stem/Full bore
- Investment casting
- CE PED tested with test report 3.1 EN 10204

No.	PART	MATERIAL
1	BODY	ASTM-A351-CF8M
2	CAP	ASTM-A351-CF8M
3	BALL	ASTM-A351-CF8M
4	SPINDEL	SS316
5	BALL SEAT	PTFE
6	STEM GASKET	PTFE
7	STEM PACKING	PTFE
8	GLAND	SS304
9	HANDLE	SS304
10	WASHER	SS304
11	STEM NUT	A194-8
12	PLASTIC COVER	PLASTIC
13	SPRING WASHER	SS304
14	HEX NUT	A194-8
15	BOLT	A193-B8

RP	Art. Nr.	W	H	L	D
		mm			
1/4"		104	51	64	11
3/8"	0188.0102	104	51	64	12.5
1/2"	0188.0103	110	50	64	15
3/4"	0188.0104	110	53	71	20
1"	0188.0105	145	68	83	25
1 1/4"	0188.0106	145	73	98	32
1 1/2"	0188.0107	180	86	108	38
2"	0188.0108	180	94	126	50

